

A3 MONOCHROME MULTI-FUNCTION PRINTER

SPECIFICATIONS

WORKFORCE ENTERPRISE WF-M21000

Model Number	WF-M21000
Printing	
Printing Technology	PrecisionCore™ Heat-Free Technology
Nozzle Configuration	8,676 nozzles (Black)
Maximum Resolution	600 x 2,400 dpi
Default Black Resolution	600 x 1,200 dpi
Minimum Ink Droplet Volume	4.4 pl
Print Speed	
ISO 24734, A4, Simplex / Duplex	Approx. 100 ipm
ISO 24734.2, A3, Simplex	Approx. 54.3 ipm
ISO 24734.2, A3, Duplex	Approx. 36.3 ipm
First Page Out Time	Approx. 6.2 sec
Printer Language	ESC/P-R, ESC/P-RJ, ESC/Page, ESC/Page-Colour, PostScript3
Printer Control Language Emulations	PCL5c / PCL6 / PostScript3 / PDF (ver 1.7)
Recommended Monthly Print Volume ⁸	20,000 - 100,000 pages per month
Maximum Monthly Duty Cycle ⁹	400,000 pages per month
HDD Capacity	320GB (encrypted)
Automatic 2-sided printing	Yes
Copying	
Copy Speed	
ISO 29183, A4, Simplex (Flatbed)	Approx. 100 ipm
ISO 24735, A4, Simplex (ADF 1:1)	Approx. 100 ipm
ISO 24735, A4, Duplex (ADF 1:2 / 2:2)	Approx. 95 ipm
Maximum Copies from Standalone	9,999 copies
Maximum Copy Resolution	600 x 1,200 dpi
Reduction / Enlargement	25 - 400%, Auto Fit Function
Copy Paper Size (Flatbed)	A3, B4, Legal, Letter, A4, B5, A5, B6, A6, 16K, 8K, Envelopes: #10, DL, C4, C5, C6
Maximum Copy Size	A3
Scanning	
Scanner Type	Flatbed colour image scanner
Sensor Type	Colour CIS
Optical Resolution	600 x 1,200 dpi
Maximum Scan Area	297.18 x 431.8 mm (11.7 x 17")
Scanner Bit Depth	
Colour	10-bit input, 8-bit output
Grayscale	10-bit input, 8-bit output
Black & White	10-bit input, 1-bit output
Scan Features	Scan to Memory Device, Scan to Network Folder/FTP, Scan to Email, Scan to Computer (Document Capture Pro), Scan to Computer (WSD)
Scan Speed (Monochrome / Colour)	
Flatbed 200 dpi	A4: 3.7 sec, A3: 4.7 sec
ADF 200 dpi (ISO 17991, Scan to Folder)	A4 (Simplex / Duplex): 60 ppm / 110 ipm, A3 (Simplex / Duplex): 30 ppm / -
ADF Function	
Support Paper Weight	52-128 g/m ²
Paper Capacity	150 sheets (80 g/m ²)
Automatic 2-sided Scan / Copy	Yes
Support Paper Size	A6 - A3
Paper Handling⁴	
Number of Paper Trays (Standards)	5 (Paper Cassettes: 4, MP Tray: 1)
Paper Hold Capacity	
Input Capacity	Up to 2,350 sheets (80 g/m ²) (Paper Cassettes 1 - 4: 550 x 4 + MP Tray: 150 sheets)
Maximum Input Capacity	Up to 5,350 sheets (80 g/m ²) (Paper Cassettes 1 - 4: 550 x 4 + MP Tray: 150 sheets + High Capacity Feeder Unit: 3,000 sheets)
Output Capacity	Up to 700 sheets (80 g/m ²) (Face Down Tray: 550 sheets, Face Up Tray: 150 sheets)
Maximum Output Capacity	Up to 4,900 sheets (80 g/m ²) (Face Down Tray: 550 sheets, Face Up Tray: 150 sheets)
Support Paper Size	A3+, A3, A4, B5, A5, A6, 5x7", 4x6", Legal, Letter, Envelopes: #10, DL, C6, C4
Maximum Paper Size	Paper Cassettes 1 - 4: A3 MP Tray: A3+, 330 x 1200mm (12.95 x 47.24")
Support Paper Weight	Paper Cassettes 1 - 4: 60 - 160 g/m ² MP Tray: 60 - 350 g/m ²

Dimensions & Weight WF-M21000

Weight (including supplies): 186.1 kg (410.3 lb)



⁴Workforce printers will not support photo glossy paper

SPECIFICATIONS

WORKFORCE ENTERPRISE WF-M21000



Size	
Size (WXDXH)w/Staple Finisher	2183 x 757 x 1243 mm
Size (WXDXH)w/Booklet Finisher	2364 x 757 x 1243 mm
Finisher	
Staple finisher	Shift/Punch/ Staple
Booklet Finisher	Shift/Punch/Saddle stitch
Network Port	
Std 1 port; Opt : 1 port	
Fax Port	
Opt 3 ports	
Printer Interface	
USB	USB 3.0
Network	Ethernet (1000BASE-T/100BASE-TX/10BASE-T), Wi-Fi (IEEE 802.11b/g/n), Wi-Fi Direct, NFC
Network Protocol	TCP/IPv4, TCP/IPv6
Network Printing Protocol	LPD, IPP, PORT9100, WSD
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD
Security Features	Limit Access Function, PIN No. Certification, LDAP Address Book, IP Address Filtering, Panel Admin Mode
USB Host Function	
Type of Direct Printing	Memory Devices
USB Host	USB Host (Scan to memory device / Storage function)
Direct Print Paper Size	A3+, A3, B4, Legal, Letter, A4, B5, A5, B6, A6, 16K, 8K, Envelopes: #10, DL, C4, C5, C6
Mobile and Remote Printing	
Epson Connect	Epson iPrint, Epson Email Print, Remote Print Driver, Scan to Cloud
Other Mobile Solutions	Google Cloud Print, Mopria Print Service
Control Panel	
LCD Screen	22.7 cm (9") TFT Colour LCD
Printer Software	
Operating System Compatibility	Windows XP / Vista / 7 / 8 / 8.1 / 10
	Windows Server 2003 / 2008 / 2012 / 2016 / 2019
	Only printing and scanning functions are supported for Windows Server OS. Bundled applications are not supported.
	Mac OS X 10.6.x or later
Server-less authentication (Sho-senzo)	Supported
Electrical Specifications	
Rated Voltage	100-240 V Universal
Rated Frequency	50-60 Hz
Power Consumption (Main Unit only)	Operating
	180 W
	Standby
	77 W
Sleep	1.4 W
	Power off
	0.4 W
Noise Level	
PC Printing / Plain Paper Default	7.5 B(A), 59 dB(A)
Consumables	
Ink Cartridge, BK, 100 PPM	C13T04Q100

© 2021 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S and other countries. App Store is a service mark of Apple Inc. Android is a trademark of Google Inc.

Information correct at time of printing
Printed July 2023.



Corporate office:

FBD One Tower, 1st Floor, Faridabad By Pass Road, Delhi Badarpur Border, Faridabad, Haryana – 121003, India

+91 98672 19344 | Email: sales@insightwithin.com | support@insightwithin.com



DELHI | MUMBAI | CHENNAI | KOCHI | BENGALURU | HYDERABAD | PUNE | AHMEDABAD | SURAT | KOLKATA | COIMBATORE | BHUBANESWAR

insightwithin | insightprints | insightwithin